



Door heater PA1006

For increased comfort inside the door

PA1006 is a compact door heater which heats the incoming air and gives increased comfort on the inside. When wall mounted, the unit can act as a high level fan heater.

- Integrated selector for the fan and heating.
- Compact and easily positioned.
- Easy installation with 1,8 m cable and plug.
- Low sound level.
- The unit is easily angled on the bracket, which is used for both wall and ceiling mounting.
- Corrosion proof housing made of hot zinc-plate and powder enamelled steel panels. Colour front: white, RAL 9016, NCS S 0500-N. Colour grille, rear section, ends and brackets: grey, RAL 7046.

⚡ Electrical heat - PA1006 (IP20)

Type	Output	Airflow	Δt^{*1}	Sound power ^{*2}	Sound pressure ^{*3}	Voltage	Amperage	Length	Weight
	[kW]	[m ³ /h]	[°C]	[dB(A)]	[dB(A)]	[V]	[A]	[mm]	[kg]
PA1006E03	0/1,5/3	230	39	60	44	230V~	13,5	650	5,3

*1) Δt = temperature rise of passing air at maximum heat output and highest airflow.

*2) Sound power (L_{WA}) measurements according to ISO 27327-2: 2014, Installation type E.

*3) Sound pressure (L_{pA}). Conditions: Distance to the unit 5 metres. Directional factor: 2. Equivalent absorption area: 200 m².

Approved for 220V/1ph/60Hz. Product performance for 220V/1ph/60Hz will differ from stated data.

Dimensions

