



SPIRA	
Material	steel pipes \varnothing 22 mm / steel profiles D1/2 52 x 37 mm
Connection thread	4 x G1/2"
Testing overpressure	0,65 MPa
Max. operating overpressure	0,5 MPa
Max. operating temperature	110 °C
Number of pipes	14, 22, 33



SPIRA 1180 x 600

Type H/L [mm]	Depth B [mm]	Weight [kg]	Water capacity [l]	Temperature exponent [n]	Heating Output [W]			Recommended power input chrome [W]		Connection span [mm]
					75/65/20 °C	70/55/20 °C	55/45/20 °C			
730/500	37	6,4	4,5	1,260	312	254	164	300	200	429
730/600	37	7,3	5,0	1,260	366	298	192	400	300	529
1180/500	37	10,2	7,1	1,277	486	395	253	500	300	429
1180/600	37	11,6	7,9	1,277	569	462	296	600	400	529
1765/500	37	15,2	10,7	1,260	722	588	379	700	500	429
1765/600	37	17,3	11,8	1,260	846	689	444	900	600	529

Thermal power measuring follows in accordance with EN 442.
 Chrome surface treatment reduces heating capacity by ~30 %.
 Accessories (page 64, 65 and 66) is not part of the radiator.

POSSIBILITY OF THE MIDDLE CONNECTION (per order)

direct middle connection standard

direct middle connection with cover

Connection options

	A [mm]	X [mm]
Plastic brackets (RAL 9006, 9016)	92-102	73-83
Metal brackets (Other colours)	88-98	69-79

DSPI 0730 0500...
DSPI 0730 0600...

DSPI 1180 0500...
DSPI 1180 0600...

DSPI 1765 0500...
DSPI 1765 0600...