

Ururu streamer technology air purifier

MCK70YV



Humidification



Flash Streamer

Humidification and air purification in one

- › Air purification for large spaces such as residential and light commercial applications
- › Pure air thanks to Daikin 'Catch and Clean' approach in decomposing harmful substances
- › High performance electrostatic HEPA filter with no need to change for 10 years
- › Whisper quiet

MCK70YV




MCK70YV-YB

Indoor Unit			MCK	70YV
Application				Floor standing type
Applicable room area			m ²	48 (1) / 96 (2) / 375 (3)
Dimensions	Unit	HeightxWidthxDepth	mm	600 x395 x287
Weight	Unit		kg	12.5
Casing	Colour			White (N9.0)
Fan	Type			Multi Blade Fan (Sirocco fan with shroud assembly)
	Air flow rate	Air purifying operation	Silent/Low/Medium/Turbo	m ³ /h 60 /132 /210 /420
		Humidifying operation	Silent/Low/Medium/Turbo	m ³ /h 102 /132 /210 /420
Sound pressure level	Air purifying operation	Silent/Low/Medium/Turbo	dBA	18 /27 /37 /54
	Humidifying operation	Silent/Low/Medium/Turbo	dBA	23 /27 /37 /54
Humidifying operation	Power input	Silent/L/M/Turbo	kW	0.011 /0.012 /0.018 /0.068
	Humidification	Turbo	ml/h	650
	Water tank capacity		l	3.6
Air purifying operation	Power input	Silent/L/M/Turbo	kW	0.008 /0.010 /0.016 /0.066
Deodorizing method				Flash streamer + Deodorizing catalyst
Dust collecting method				Electrostatic HEPA filter
Air filter	Type			Polyethylene terephthalate net
Sign	Item	01		Dust sensor lamp: 3 stages // PM 2.5 sensor lamp: 3 stages / Odour sensor lamp: 3 stages // Humidity monitor : 20% - 90% / Humidity setting: Low/Standard/High / Airflow rate: Quiet/Low/Standard/Turbo / AUTO FAN mode / Econo mode / Anti-pollen mode / MOIST mode / CIRCULATION mode / Water supply lamp / Streamer lamp / Recommendation mode lamp / Humidifier ON/OFF lamp / Sleep mode / Child proof lock lamp
Power supply	Phase/Frequency/Voltage		Hz/V	1~/50/60/220-240/220-230
Type				Humidifying air purifier

(1) The coverage area is appropriate for operating the unit of maximum fan speed (HH). Coverage area indicates the space where a certain amount of dust particles can be removed in 30 minutes. | (2) Converted to NRCC standards from test values in accordance with JEM1467. | (3) Converted to CADR standards from test values in accordance with JEM1467. | Operating sound levels are the average of values measured at 1m away from the front, left, right and top of the unit. (These are equal to the values in an anechoic chamber) | Humidification amount changes in accordance with indoor and outdoor temperature and humidity. Measurement condition: 20°C in temperature, 30% in humidity. | Electrostatic HEPA filter and humidifying filters are attached in the unit. | Requirements according to JEM1467.

Daikin Europe Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · <https://www.daikin.eu> · RPR Oostende (Responsible Editor)



ECPEN21-745A

11/2021

The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. / Daikin Central Europe HandelsGmbH. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH have compiled the content of this publication to the best of their knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.

