



Pol. Ind. Pla de la Bruguera C/ Olot, 18
Castellar del Vallès 08211 (Barcelona)
Tel. (+34) 937143535 @: info@chquimica.com
www.chquimica.com
Registro Industrial: 154069

REF.: 103162

AIR FIRE

Heat sink for welding. Thermal protector



DESCRIPTION

AIR FIRE® is a product specially formulated for the protection of surfaces close to welding areas. It dissipates heat, avoiding burns, deformations and other undesirable effects of a high heat point. It absorbs heat by evaporating it. Protects sensitive materials such as wood, tiles, aluminium, glass, synthetic materials, rubbers, seat gaskets, etc.
Its special molecular structure means that the product can be sprayable and gel at the same time. Adheres well to vertical surfaces.

HOW TO USE

AIR FIRE® is used neat on the surface to be protected (wood, tiles, aluminium, glass, synthetic materials). Spray the areas close to the weld.

It should be used pure, without dilutions.

APPLICATION

Ideal product for plumbing, heating and cooling, air conditioning and for industry in general. For soft, hard, autogenous, argon welding processes, etc.

FORMAT

750 ml bottle
Box of 12 units
Pallets of 36 boxes

Warnings

The suggestions and recommendations on the use of our products respond to our best knowledge and understanding at the time of writing this technical sheet. We are not responsible for any possible negligence in its handling. Compliance with all legal provisions, including those existing regarding the protection of industrial property, is exclusively the responsibility of the users of our products.

PHYSICAL PROPERTIES

APPEARANCE – GEL-PASTE
COLOUR – COLOURLESS
DENSITY – MIN. 1.008/MAX. 1.029
PH 100% – 7.97
FLASH POINT – NON-FLAMMABLE